



**BASTA!**  
NET, WINDOWS, VISUAL STUDIO

# Besseres C#

## Workshop

BASTA! Spring 2014

# Async und Parallel

Workshop



Rainer Stropek

software architects gmbh

Web <http://www.timecockpit.com>  
Mail [rainer@timecockpit.com](mailto:rainer@timecockpit.com)  
Twitter @rstropek



**time cockpit**  
Saves the day.

# Async Programming

In C# and .NET 4.5

```
private static void DownloadSomeTextSync()
{
    using (var client = new WebClient())
    {
        Console.WriteLine(
            client.DownloadString(new Uri(string.Format(
                "http://{0}",
                (Dns.GetHostAddresses("www.basta.net"))[0]))));
    }
}
```

# Synchronous

## *AsyncResult* Pattern

```
private static void DownloadSomeText()
{
    var finishedEvent = new AutoResetEvent(false);

    // Notice the AsyncResult-pattern here
    Dns.BeginGetHostAddresses("www.basta.net", GetHostEntryFinished,
        finishedEvent);
    finishedEvent.WaitOne();
}

private static void GetHostEntryFinished(AsyncResult result)
{
    var hostEntry = Dns.EndGetHostAddresses(result);
    using (var client = new WebClient())
    {
        // Notice the Event-based asynchronous pattern here
        client.DownloadStringCompleted += (s, e) =>
        {
            Console.WriteLine(e.Result);
            ((AutoResetEvent)result.AsyncState).Set();
        };
        client.DownloadStringAsync(new Uri(string.Format(
            "http://{0}",
            hostEntry[0].ToString())));
    }
}
```

```

private static void DownloadSomeText()
{
    var finishedEvent = new AutoResetEvent(false);

    // Notice the IAsyncResult-pattern here
    Dns.BeginGetHostAddresses(
        "www.basta.net",
        (result) =>
        {
            var hostEntry = Dns.EndGetHostAddresses(result);
            using (var client = new WebClient())
            {
                // Notice the Event-based asynchronous pattern here
                client.DownloadStringCompleted += (s, e) =>
                {
                    Console.WriteLine(e.Result);
                    ((AutoResetEvent)result.AsyncState).Set();
                };
                client.DownloadStringAsync(new Uri(string.Format(
                    "http://{0}",
                    hostEntry[0].ToString())));
            }
        },
        finishedEvent);
    finishedEvent.WaitOne();
}

```

# *IAsyncResult* Pattern

With Lambdas

```
private static void DownloadSomeTextUsingTask()
{
    Dns.GetHostAddressesAsync("www.basta.net")
        .ContinueWith(t =>
        {
            using (var client = new WebClient())
            {
                return client.DownloadStringTaskAsync(
                    new Uri(string.Format(
                        "http://{0}",
                        t.Result[0].ToString())));
            }
        })
        .ContinueWith(t2 => Console.WriteLine(t2.Unwrap().Result))
        .Wait();
}
```

## TPL

Notice the use of the new Task Async Pattern APIs in .NET 4.5 here

# Rules For Async Method Signatures

- ▶ Method name ends with **Async**

- ▶ Return value

  - Task** if sync version has return type **void**

  - Task<T>** if sync version has return type **T**

- ▶ Avoid **out** and **ref** parameters

  - Use e.g. **Task<Tuple<T1, T2, ...>>** instead



```
// Synchronous version
private static void DownloadSomeTextSync()
{
    using (var client = new WebClient())
    {
        Console.WriteLine(
            client.DownloadString(new Uri(string.Format(
                "http://{0}",
                (Dns.GetHostAddresses("www.basta.net"))[0]))));
    }
}

// Asynchronous version
private static async void DownloadSomeTextUsingTaskAsync()
{
    using (var client = new WebClient())
    {
        Console.WriteLine(
            await client.DownloadStringTaskAsync(new Uri(string.Format(
                "http://{0}",
                (await Dns.GetHostAddressesAsync("www.basta.net"))[0]))));
    }
}
```

## Sync vs. Async


Notice how similar the sync and async versions are!

```

private static async void DownloadSomeTextUsingTaskAsync2()
{
    using (var client = new WebClient())
    {
        try
        {
            var ipAddress = await Dns.GetHostAddressesAsync("www.basta.net");
            var content = await client.DownloadStringTaskAsync(
                new Uri(string.Format("http://{0}", ipAddress[0])));
            Console.WriteLine(content);
        }
        catch (Exception)
        {
            Console.WriteLine("Exception!");
        }
    }
}

```

## Generated Code



# Guidelines for `async/await`

- ▶ If `Task` ended in `Canceled` state, `OperationCanceledException` will be thrown

```
private async static void CancelTask()
{
    try
    {
        var cancelSource = new CancellationTokencSource();
        var result = await DoSomethingCancelledAsync(cancelSource.Token);
        Console.WriteLine(result);
    }
    catch (OperationCanceledException)
    {
        Console.WriteLine("Cancelled!");
    }
}

private static Task<int> DoSomethingCancelledAsync(CancellationTokenc token)
{
    // For demo purposes we ignore token and always return a cancelled task
    var result = new TaskCompletionSource<int>();
    result.SetCanceled();
    return result.Task;
}
```


# TPL

TaskCompletionSource<T>

```

private static async void DownloadSomeTextUsingTaskAsync2()
{
    using (var client = new WebClient())
    {
        try
        {
            var ipAddress = await Dns.GetHostAddressesAsync("www.basta.net");
            new Thread(() =>
            {
                Thread.Sleep(100);
                client.CancelAsync();
            }).Start();
            var content = await client.DownloadStringTaskAsync(
                new Uri(string.Format("http://{0}", ipAddress[0])));
            Console.WriteLine(content);
        }
        catch (Exception)
        {
            Console.WriteLine("Exception!");
        }
    }
}

```


**WebException was caught**

The request was aborted: The request was canceled.

**Troubleshooting tips:**

- [Check the Response property of the exception to determine the status of the request.](#)
- [Check the Status property of the exception to determine the status of the request.](#)
- [Get general help for this exception.](#)

[Search for more Help Online...](#)

**Exception settings:**

☐ Break when this exception type is thrown

**Actions:**

- [View Detail...](#)
- [Copy exception detail to the clipboard](#)
- [Open exception settings](#)

Note that async API of webClient uses existing cancellation logic instead of CancellationTokenSource

```
namespace ConsoleApplication2
{
    class Program
    {
        static void Main(string[] args)
        {
            try
            {
                Task.WaitAll(new[] {
                    Task.Run(() =>
                    {
                        Thread.Sleep(1000);
                        throw new ArgumentException();
                    }),
                    Task.Run(() =>
                    {
                        Thread.Sleep(2000);
                        throw new InvalidOperationException();
                    })
                });
            }
            catch (Exception ex)
            {
                Console.WriteLine(ex);
            }
        }
    }
}
```



#### AggregateException was caught

One or more errors occurred.

#### Troubleshooting tips:

[Get general help for exceptions.](#)

[Get general help for the inner exception.](#)

[Search for more Help Online...](#)

#### Exception settings:

☐ Break when this exception type is thrown

#### Actions:

[View Detail...](#)

[Copy exception detail to the clipboard](#)

[Open exception settings](#)

# Guidelines for `async/await`

- ▶ Caller runs in parallel to awaited methods
- ▶ Async methods sometimes do not run async (e.g. if task is already completed when `async` is reached)

## Guidelines for **async/await** (UI Layer)

- ▶ **async/await** use **SynchronizationContext** to execute the awaiting method → UI thread in case of UI layer
- ▶ Use **Task.ConfigureAwait** to disable this behavior  
E.g. inside library to enhance performance



# Async/await im UI

```
public partial class MainWindow : Window
{
    public MainWindow()
    {
        this.DataContext = this;
        this.ListBoxContent = new ObservableCollection<string>();
        this.InitializeComponent();
        this.ListBoxContent.Add("Started");

        this.Loaded += async (s, e) =>
        {
            for (int i = 0; i < 10; i++)
            {
                ListBoxContent.Add(await Task.Run(() =>
                {
                    Thread.Sleep(1000);
                    return "Hello World!";
                }));
            }

            this.ListBoxContent.Add("Finished");
        };
    }
}

public ObservableCollection<string> ListBoxContent { get; private set; }
```

Visual Studio screenshot showing a C# code file with an exception. The code is:

```
this.Loaded += async (s, e) =>
{
    for (int i = 0; i < 10; i++)
    {
        ListBoxContent.Add(await Task.Run(() =>
        {
            Thread.Sleep(1000);
            return "Hello World!";
        }).ConfigureAwait(false));
    }

    this.ListBoxContent.Add("Finished");
};
```

The exception message is:

**NotSupportedException occurred**  
This type of CollectionView does not support changes to its SourceCollection from a thread different from the Dispatcher thread.

**Troubleshooting tips:**  
[Check to determine if there is a class that supports this functionality.](#)  
[Get general help for this exception.](#)  
[Search for more Help Online...](#)

**Exception settings:**  
☒ Break when this exception type is thrown

**Actions:**  
[View Detail...](#)  
[Enable editing](#)  
[Copy exception detail to the clipboard](#)  
[Open exception settings](#)

The Threads window shows the following threads:

ID	Managed ID	Category	Name	Location	Priority
4504	0	Worker Thread	<No Name>	<not available>	Highest
4360	6	Worker Thread	<No Name>	<not available>	Normal
1784	7	Worker Thread	vshost.RunParkingWindow	▼ [Managed to Native Transition]	Normal
2972	9	Main Thread	Main Thread	▼ [Managed to Native Transition]	Normal
2412	8	Worker Thread	.NET SystemEvents	▼ [Managed to Native Transition]	Normal
4356	10	Worker Thread	Stylus Input	▼ [Managed to Native Transition]	Normal
4140	3	Worker Thread	<No Name>	▼ WpfAwaitDemo.MainWindow..ctor	Normal
2644	0	Worker Thread	<No Name>	<not available>	Normal

## Guidelines For Implementing Methods Ready For **async/await**

- ▶ Return **Task/Task<T>**
- ▶ Use postfix **Async**
- ▶ If method support cancelling, add parameter of type **System.Threading.CancellationToken**
- ▶ If method support progress reporting, add **IProgress<T>** parameter
- ▶ Only perform very limited work before returning to the caller (e.g. check arguments)
- ▶ Directly throw exception only in case of *usage* errors

```
public class Program : IProgress<int>
{
    static void Main(string[] args)
    {
        var finished = new AutoResetEvent(false);
        PerformCalculation(finished);
        finished.WaitOne();
    }

    private static async void PerformCalculation(AutoResetEvent finished)
    {
        Console.WriteLine(await CalculateValueAsync(
            42,
            CancellationToken.None,
            new Program()));
        finished.Set();
    }

    public void Report(int value)
    {
        Console.WriteLine("Progress: {0}", value);
    }
}
```

# Progress Reporting

# Cancellation

```
private static Task<int> CalculateValueAsync(
    int startingValue,
    CancellationToken cancellationToken,
    IProgress<int> progress)
{
    if (startingValue < 0)
    {
        // Usage error
        throw new ArgumentOutOfRangeException("startingValue");
    }

    return Task.Run(() =>
    {
        int result = startingValue;
        for (int outer = 0; outer < 10; outer++)
        {
            cancellationToken.ThrowIfCancellationRequested();

            // Do some calculation
            Thread.Sleep(500);
            result += 42;

            progress.Report(outer + 1);
        }

        return result;
    });
}
```

```
private static async void PerformCalculation(AutoResetEvent
finished)
{
    try
    {
        var cts = new CancellationTokensource();
        Task.Run(() =>
        {
            Thread.Sleep(3000);
            cts.Cancel();
        });
        var result = await CalculateValueAsync(
            42,
            cts.Token,
            new Program());
    }
    catch (OperationCanceledException)
    {
        Console.WriteLine("Cancelled!");
    }

    finished.Set();
}
```

# Cancellation

```
private static Task<int> CalculateValueAsync(  
    int startingValue,  
    CancellationToken cancellationToken,  
    IProgress<int> progress)  
{  
    if (startingValue < 0)  
    {  
        // By definition the result has to be 0 if startingValue < 0  
        return Task.FromResult(0);  
    }  
  
    return Task.Run(() =>  
        {  
            [...]  
        }));  
}
```

## *Task.FromResult*

Note how *Task.FromResult* is used to return a pseudo-task

Note that you could use *TaskCompletionSource* instead

```
namespace MvcApplication2.Controllers
{
    public class BlogController : ApiController
    {
        // GET api/values/5
        public async Task<BlogItem> Get(int id)
        {
            // Open context to underlying SQL database
            using (var context = new BlogContext())
            {
                // Make sure that it contains database
                await context.GenerateDemoDataAsync();

                // Build the query
                var blogs = context
                    .BlogItems
                    .Where(b => b.BlogId == id);

                // Execute query
                return await blogs.FirstOrDefaultAsync();
            }
        }
    }
}
```

## Async Web API



```
namespace MvcApplication2.Tests.Controllers
{
    [TestClass]
    public class BlogControllerTest
    {
        [TestMethod]
        public async Task GetById()
        {
            BlogController controller = new BlogController();

            var result = await controller.Get(1);
            Assert.IsNotNull(result);

            result = await controller.Get(99);
            Assert.IsNull(result);
        }
    }
}
```

## Async Unit Test

BASTA! Spring 2014

Q&A

Thank your for coming!



Rainer Stropek

software architects gmbh

Mail  
Web  
Twitter

rainer@timecockpit.com  
<http://www.timecockpit.com>  
@rstropek



**time cockpit**  
Saves the day.



**time cockpit** is the leading time tracking solution for knowledge workers. Graphical time tracking calendar, automatic tracking of your work using signal trackers, high level of extensibility and customizability, full support to work offline, and SaaS deployment model make it the optimal choice especially in the IT consulting business.

Try **time cockpit** for free and without any risk. You can get your trial account at <http://www.timecockpit.com>. After the trial period you can use **time cockpit** for only 0,20€ per user and day without a minimal subscription time and without a minimal number of users.



**time cockpit** ist die führende Projektzeiterfassung für Knowledge Worker. Grafischer Zeitbuchungskalender, automatische Tätigkeitsaufzeichnung über Signal Tracker, umfassende Erweiterbarkeit und Anpassbarkeit, volle Offlinefähigkeit und einfachste Verwendung durch SaaS machen es zur Optimalen Lösung auch speziell im IT-Umfeld.

Probieren Sie **time cockpit** kostenlos und ohne Risiko einfach aus. Einen Testzugang erhalten Sie unter <http://www.timecockpit.com>. Danach nutzen Sie **time cockpit** um nur 0,20€ pro Benutzer und Tag ohne Minstdauer und ohne Mindestbenutzeranzahl.